



# U-Station Specification

version 1.0 2013/06/21

## Mechanical

Main Dimensions (WxHxL).....	230x310(530 <sup>1</sup> )x110 mm
Mechanical mounting.....	Standard photography plate
Tripod height.....	710 mm/ 2000 mm.
Main Box weight.....	2300 g
Tripod weight.....	2600 g
USB connector.....	IP68 Ruggeded USB Type B <sup>2</sup>
Charging connector.....	2-way MIL-C-5015-10SL
Joystick interface.....	3-way MIL-C-5015-10SL
Radio Connector.....	SMA female
Temperature Range.....	-30 °C to +85°C

## Electrical

Supply.....	NiMH/LiFe Battery
.....	Optional external +12VDC supply
Power Consumption.....	12 W
Voltmeter.....	0-20 V

## Telemetry

Frequency .....	<b>900MHz</b> /1.4 Ghz/2.4GHz <sup>3</sup>
Power.....	1 W
Range.....	100 km / 80km / 40 km
baud rate.....	115200 bps
Data Ouptut to PC.....	USB FTDI Interface

## Emitter Interface

Type.....	3 ways MIL-C-5015-10SL
Protocol.....	PCM 1024Z at 3.3V TTL
Recommended Futaba emitter.....	Futaba T7CP

## Video Receiver

Frequency.....	<b>1.2-1.3 GHz</b> /2.4Ghz/5.8GHz <sup>4</sup>
Antenna directivity.....	15 dBi
Data Output to PC.....	USB connection

1 With Telemetry antenna connected  
2 Connector is compatible with standard non-ruggeded USB cables.

3 Depending on local legislation  
4 Depending on local legislation